



NEVSP40

CREE



CRI 90



adjusted trim



fixed trim



square trim



trim-less trim

Specific characteristics



Die-casting aluminum material



CRI>90



Dimmable driver for option



Different colors for Anti-glare ring



Serialized products, multiple dimensions for choice



3 years warranty

COB

CRI >90

15°

24°

38°

55°

3000K

4000K

5000K

IP20

200-240V



TECHNICAL DETAILS:


Model	Watts	Lumens	Color Temp	Cutout(mm)
NEVSP40-3	9W	800lm	3000K/4000K/5000K	Ø75
NEVSP40-3	15W	1300lm	3000K/4000K/5000K	Ø75
NEVSP40-4	24W	2050lm	3000K/4000K/5000K	Ø100
NEVSP40-5	33W	3000lm	3000K/4000K/5000K	Ø125
NEVSP40-6	42W	3850lm	3000K/4000K/5000K	Ø150




Model	A(mm)	B(mm)
NEVSP40-3	85	52
NEVSP40-3/S	85*85	89
NEVSP40-4	112	64
NEVSP40-4/S	112*112	140
NEVSP40-5	140	78
NEVSP40-5/S	140*140	169
NEVSP40-6	165	86
NEVSP40-6/S	165*165	86

Photometric Data


NEVSP40 9W 24°



NEVSP40 15W 24°



NEVSP40 24W 24°



NEVSP40 33W 24°

