

NEVSP80



OPTIONS:

- Beam angle: 20° 40°
- 10 different bezels available and are to be ordered as separate items
- Adjustable angle 20°(NEVSP80D001/002/004/006)
- Waterproof bezel is available to choose

CONSTRUCTION:

- Die-cast aluminum housing and heat sink
- Clear PMMA front cover
- White painted die-cast aluminum bezels
- Separate driver included




APPLICATIONS:

- Bars and restaurants
- Hotels
- Meeting rooms and corridors
- High-specification residential projects


TECHNICAL DETAILS:

Model	Watts	Color Temp	Lumens	CRI	Input
NEVSP80	7W	3000K/6500K	525lm	>80	220-240V
NEVSP80	10W	3000K/6500K	750lm	>80	220-240V
NEVSP80	13W	3000K/6500K	950lm	>80	220-240V
NEVSP80	15W	3000K/6500K	1125lm	>80	220-240V

Photometric Data



Watts	A	B
7W/10W	Ø50	59
13W/15W	Ø50	86



Model	C	D	Cutout
NEVSP80-1	85	37	Ø75
NEVSP80-2	108	33	Ø95
NEVSP80-3	84	62	Ø75
NEVSP80-4	100	60	Ø90
NEVSP80-5	84	62	Ø75
NEVSP80-6	100	60	Ø90
NEVSP80-7/-9	85	69.5	Ø75
NEVSP80-8	85	69.5	Ø75
NEVSP80-10	85	69.5	Ø75
NEVSP80-11	85	52	Ø75